

## Polyurethane Cast Iron Plate Swivel Castor 75mm 140kg Load

**Product code: JAB75PTBJ**

Open screw thread jacking castor with side fitting nuts with 160mm lift fitted with a 75mm white zinc plated swivel pressed steel castor with a brown polyurethane tyred cast iron centred wheel with a ball bearing bore and a load capacity of 140kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in bending the thread but more likely the castor will tear away from the screw thread. Please refer to the BIL catalogue or request a drawing



Diameter (mm)	75
Castor Height (mm)	108
Castor Type	Swivel
Swivel Radius (mm)	70
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	12
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	140
Tread (mm)	40
Height (mm)	418
Lifting Stroke (mm)	160

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

