T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Polyurethane Nylon Bolt Hole Swivel Castor Brake 100mm 150kg Load

Product code: SSMM100NPBH12SWB



Grade 304 Pressed stainless steel swivel castor with bolt hole fixing fitted with a polyurethane tyre nylon centred wheel with plain bore and swivel wheel brake. Wheel diameter 100mm, tread width 30mm, overall height 128mm, 12mm bolt hole. Load capacity 150kg.

Diameter (mm)	100
Fixing Option	Bolt Hole
Castor Type	Swivel with Total Lock Brake
Height (mm)	128
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Bearing Type	Plain
Tread (mm)	30
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	12
Load Capacity (kg)	170
Temperature Resistance	-20°C to +70°C
Head Dia (mm)	76
Swivel Radius (mm)	118
Castor Material	Stainless Steel

BIL GROUP LTD
Porte Marsh Road, Calne, Wiltshire, SN11 9BW
Registered in England No: 2603821
VAT Reg: GB572705729