

## Polyurethane Nylon Bolt Hole Swivel Castor Brake 125mm 250kg Load

**Product code: SSEH125NPBH12SWB**

Grade 304 Pressed stainless steel swivel castor with a 12mm bolt hole fitted with a red polyurethane tyred white nylon centred wheel with a plain bore and a total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm, Load capacity 250kg



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 125  |
| Fixing Option            | Bolt Hole                                  |
| Castor Type              | Swivel with Total Lock Brake               |
| Height (mm)              | 156  |
| Wheel Material           | Polyurethane on Nylon                      |
| Colour / Shore Hardness  | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type             | Plain                                      |
| Tread (mm)               | 35   |
| Fork Thickness (mm)      | 3  |
| To Suit Fixing Bolt (mm) | 12   |
| Load Capacity (kg)       | 300  |
| Temperature Resistance   | -20 °C TO +70 °C                           |
| Head Dia (mm)            | 78   |
| Swivel Radius (mm)       | 115  |

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

