

Polyurethane Nylon Plate Swivel Castor 80mm 150kg Load

Product code: BZRMM80NPB

Pressed steel swivel castor with top plate fixing fitted with red polyurethane tyre on white nylon centred wheel with a roller bearing. Wheel diameter 80mm, tread width 30mm, overall height 100mm, top plate 105mm x 85mm, hole centres 80mm / 72mm or x 60mm / 52mm. Load capacity 150kg.



| | |
|--------------------------|--|
| Diameter (mm) | 80 |
| Castor Type | Swivel |
| Fixing Option | Plate |
| Height (mm) | 100 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Bearing Type | Roller |
| Load Capacity (kg) | 150 |
| Tread (mm) | 30 |
| Swivel Radius (mm) | 74 |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80/72 x 60/52 |
| Top Plate Thickness (mm) | 2.5 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

