T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Polyurethane Nylon Plate Swivel Castor Brake 125mm 200kg Load



**Product code: SSMM125NPSWB**

Grade 304 Pressed steel swivel castor with top plate fixing fitted with a red polyurethane tyre on white nylon centre wheel with a plain bore and total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm, top plate 105mm x 85mm, hole centres 80mm x60mm. Load capacity 200kg.

| | |
|---|---|
| Diameter (mm) | 125 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 155 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type | Plain |
| Tread (mm) | 35 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 200 |
| Temperature Resistance | -20°C to +70°C |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 2 |
| Swivel Radius (mm) | 123 |
| Castor Material | Zinc plated |