

Polyurethane Nylon Plate Swivel Castor Brake Locking Castor 125mm 200kg Load

Product code: JAB125NPBJSWB

Open screw thread jacking castor with side fitting nuts with 160mm lift fitted with a 125mm white zinc plated swivel pressed steel castor with a red polyurethane tyred white nylon centred wheel with a ball bearing bore and a total lock brake, load capacity of 200kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in bending the thread but more likely the castor will tear away from the screw thread. Please refer to the BIL catalogue or request a drawing



| | |
|--------------------------|--|
| Diameter (mm) | 125 |
| Castor Height (mm) | 156 |
| Castor Type | Swivel with Total Lock Brake |
| Swivel Radius (mm) | 125 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 12 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Load Capacity (kg) | 200 |
| Tread (mm) | 40 |
| Height (mm) | 466 |
| Lifting Stroke (mm) | 160 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

