

Polyurethane Nylon Plate Swivel Castor Brake Locking Castor 200mm 250kg Load

Product code: JAZ200NPBJSWB

Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 200mm white zinc plated swivel pressed steel castor with a red polyurethane tyred white nylon centred wheel with ball bearing bore and total lock brake, with a load capacity of 250kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing



| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Castor Height (mm) | 238 |
| Castor Type | Swivel with Total Lock Brake |
| Swivel Radius (mm) | 167 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 14 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Load Capacity (kg) | 250 |
| Tread (mm) | 50 |
| Height (mm) | 476 / 551 |
| Lifting Stroke (mm) | 75 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

