

Polyurethane on Cast Iron Plate Fixed Castor 125mm 675kg Load

Product code: 2VFH125PTJP06

Fabricated steel twin wheel fixed castor with a top plate fixing fitted with 2 x polyurethane on cast iron centred wheels with ball journal bearings. Wheel diameter 2 x 125mm, tread width 2 x 50mm, overall height 192mm, top plate 150mm x 175mm, hole centres 105mm x 80mm or 120mm x 60mm. Load capacity 675kg.



Diameter (mm)	125
Castor Type	Fixed
Fixing Option	Plate
Height (mm)	192
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / TBC
Temperature Resistance	TBC
Bearing Type	Ball
Load Capacity (kg)	675
Tread width (mm)	2 x 50
Plate Size (mm)	150 x 175
Hole Centres (mm)	60/80 x 120/105
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	4.5
To Suit Fixing Bolt (mm)	12
Brand	Varley

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

