T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Polyurethane on Cast Iron Plate Fixed Castor 200mm 1500kg Load



Product code: 2VFH250PTJP06

Fabricated steel twin wheel fixed castor with a top plate fixing fitted with 2 x polyurethane on cast iron centred wheels with ball journal bearings. Wheel diameter 2 x 250mm, tread width 2 x 50mm, overall height 318mm, top plate 150mm x 175mm, hole centres 105mm x 80mm or 120mm x 60mm. Load capacity 1500kg.

Diameter (mm)	250
Castor Type	Fixed
Fixing Option	Plate
Height (mm)	318
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / TBC
Temperature Resistance	-20 ?C to 80 ?C
Bearing Type	Ball
Load Capacity (kg)	1500
Tread width (mm)	2 x 50
Plate Size (mm)	150 x 175
Hole Centres (mm)	60/80 x 120/105
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	4.5
To Suit Fixing Bolt (mm)	12
Brand	Varley
Castor Material	Zinc plated