

Polyurethane on Nylon Plate Stainless Steel Swivel Castor Brake 200mm 400kg Load

Product code: V82Q200PNPP05



Stainless steel swivel castor with a top plate fixing fitted with red polyurethane on white nylon centred wheel with plain bore and total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 240mm, top plate 135mm x 105mm, hole centres 105mm x 80mm or 105mm x 75mm. Load capacity 400kg.

Diameter (mm)	200
Castor Type	Swivel
Fixing Option	Plate
Height (mm)	240
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane Tyre on White Nylon Rim / 98±5 Shore A
Temperature Resistance	-5°C to 60°C
Bearing Type	Plain
Load Capacity (kg)	400
Tread width (mm)	50
Swivel Radius (mm)	153
Plate Size (mm)	135 x 105
Hole Centres (mm)	105 x 80/75
Top Plate Thickness (mm)	2.5
Fork Thickness (mm)	2.5
To Suit Fixing Bolt (mm)	10
Brand	Varley

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

