T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Puncture Proof Polyurethane Plate Fixed Castor 260mm 100kg Load



**Product code: BZFPCF260PPUD/LITE**

Fabricated fixed castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre red polypropylene centred wheel with plain bore.Wheel diameter 260, tread width 85mm, overall height 318mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 100kg.

| | |
|---|---|
| Diameter (mm) | 260 |
| Castor Type | Fixed |
| Fixing Option | Plate |
| Plate Size (mm) | 115 x 105 |
| Height (mm) | 318 |
| Hole Centres (mm) | 76/92 x 76/67 |
| Tread (mm) | 85 |
| Temperature Resistance | -10 ?C TO +60 ?C |
| To Suit Fixing Bolt (mm) | 10 |
| Bearing Type | Plain |
| Wheel Material | Puncture Proof Wheels |
| Load Capacity (kg) | 100 |
| Colour / Shore Hardness | Black Puncture Proof Tyre on Polypropylene Rims / Low PU |
| Top Plate Thickness (mm) | 5 |
| Fork Thickness (mm) | 5 |
| Castor Material | Zinc plated |