

Puncture Proof Polyurethane Plate Swivel Castor Brake 260mm 100kg Load

Product code: BZFPC260MPUBBK/LITE

Fabricated swivel castor with a top plate fixing fitted with a black ribbed pattern puncture proof tyre red steel disc centred wheel with roller bearing and side fitting wheel brake. Wheel diameter 260, tread width 85mm, overall height 318mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 100kg.



| | |
|--------------------------|--|
| Diameter (mm) | 260 |
| Castor Type | Swivel with Wheel Brake |
| Fixing Option | Plate |
| Plate Size (mm) | 115 x 105 |
| Height (mm) | 318 |
| Hole Centres (mm) | 76/92 x 76/67 |
| Swivel Radius (mm) | 198 |
| Tread (mm) | 85 |
| Temperature Resistance | -10 °C TO +60 °C |
| To Suit Fixing Bolt (mm) | 10 |
| Bearing Type | Roller |
| Wheel Material | Puncture Proof Wheels |
| Load Capacity (kg) | 100 |
| Colour / Shore Hardness | Black Puncture Proof Tyre on Steel Rims / Low PU |
| Top Plate Thickness (mm) | 5 |
| Fork Thickness (mm) | 5.5 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

