

## Puncture Proof Polyurethane Plate Swivel Castor Brake 260mm 100kg Load

**Product code: BZPC260MPUBDSWB/LITE**

Pressed steel swivel castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre on a pressed steel centre with roller bearings and total lock brake. Wheel diameter 260mm, tread width 85mm, overall height 302mm, top plate 200mm x 160mm, hole centres 150mm x 115mm. Load capacity 100kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 260  |
| Castor Type              | Swivel with Total Lock Brake                     |
| Fixing Option            | Plate  |
| Plate Size (mm)          | 200 X 160  |
| Height (mm)              | 307  |
| Hole Centres (mm)        | 150 x 115  |
| Swivel Radius (mm)       | 215  |
| Tread (mm)               | 85   |
| Temperature Resistance   | -10 °C TO +60 °C                                 |
| To Suit Fixing Bolt (mm) | 14   |
| Bearing Type             | Roller   |
| Wheel Material           | Puncture Proof Wheels                            |
| Load Capacity (kg)       | 100  |
| Colour / Shore Hardness  | Black Puncture Proof Tyre on Steel Rims / Low PU |
| Top Plate Thickness (mm) | 4  |
| Fork Thickness (mm)      | 3  |