



Removable Handle Elastic Rubber Cast Iron Plate Swivel Castor 100mm 210kg Load

Product code: JAZHS100CRBJRH

Side winding jacking unit (removable handle) with maximum lift of 200mm fitted with a Fabricated swivel castor with a top plate fixing fitted with a black 75 shore A elastic rubber tyre cast iron centred ball bearing wheel. Wheel diameter 100mm, tread width 50mm. Maximum Load for the complete unit is capacity 210kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please be aware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)



	1
Diameter (mm)	100
Castor Height (mm)	143
Castor Type	Swivel
Swivel Radius (mm)	85
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 75 Shore A
Temperature Resistance	-20 °C TO +60 °C
Load Capacity (kg)	210
Tread (mm)	50
Height (mm)	553/753
Lifting Stroke (mm)	200
Handle Option	Removable





