T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Removable Handle Polyurethane Cast Iron Plate Swivel Castor 200mm 1000kg Load



Product code: JAZHSK200PTBJRH

Side winding jacking unit (removable handle) with maximum lift of 200mm fitted with a Fabricated swivel castor with a top plate fixing fitted with a brown polyurethane tyre cast iron centred wheel with ball bearings. Wheel diameter 200mm, tread width 50mm, maximum Load for the complete unit is capacity 1000kg.Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please be aware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

Diameter (mm)	200
Castor Height (mm)	250
Castor Type	Swivel
Swivel Radius (mm)	165
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 ?C TO +80 ?C
Load Capacity (kg)	1000
Tread (mm)	50
Height (mm)	657 / 857
Lifting Stroke (mm)	200
Handle Option	Removable
Castor Material	Zinc plated