T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Rubber Swivel Castor Plate Brake 125mm 100kg



**Product code: SSM125GRBJSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a grey thermoplastic rubber tyre on polypropylene centred wheel with ball bearing and a total lock brake. Wheel diameter 125mm, tread width 32mm, overall height 156mm, top plate 90mm x 70mm, hole centres 75mm x 56mm or 64mm x 44mm. Load capacity 100kg.

| | |
|---|---|
| Diameter (mm) | 125 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 156 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 87 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 32 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 100 |
| Temperature Resistance | -15°C to +80°C |
| Plate Size (mm) | 90 x 70 |
| Hole Centres (mm) | 75/64 x 56/44 |
| Top Plate Thickness (mm) | 2 |
| Swivel Radius (mm) | 107 |
| Castor Material | Stainless Steel |