

## Soft Ergonomic Speed Polyurethane Plate Swivel Castor Brake 150mm 500kg Load

**Product code: BZXP150RSPABJSWBLP**



Pressed steel swivel castor with a top plate fixing fitted with a 75 shore A Blue Ergonomic polyurethane tyre on aluminium centred wheel with ball bearings and a total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 500kg at 4kph and 200kg at 16kph **\*\*FOR INTERNAL TOWING ONLY\*\***

|                          |   |
|--------------------------|---|
| Diameter (mm)            | 150   |
| Height (mm)              | 200   |
| Fixing Option            | Plate   |
| Castor Type              | Swivel with Total Lock Brake                              |
| Swivel Radius (mm)       | 180   |
| Bearing Type             | Ball  |
| Plate Size (mm)          | 162 X 140   |
| Hole Centres (mm)        | 140 X 105   |
| Wheel Material           | Polyurethane on Aluminium                                 |
| Colour / Shore Hardness  | Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A |
| Tread (mm)               | 50  |
| Load Capacity (kg)       | 500   |
| Top Plate Thickness (mm) | 6   |
| Fork Thickness (mm)      | 5   |
| To Suit Fixing Bolt (mm) | 10  |
| Temperature Resistance   | -20 °C TO +70 °C  |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

