


## Soft Speed Polyurethane Plate Swivel Castor 200mm 700kg Load

**Product code: BZXP200SPABJLP**



Pressed steel swivel castor with a top plate fixing fitted with a blue 75 shore A polyurethane tyre on aluminium centred wheel with ball bearings. Wheel diameter 200mm, tread width 50mm, overall height 245mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 700kg at 4kph and 280kg at 16kph **\*\*FOR INTERNAL TOWING ONLY\*\***

Diameter (mm)	200
Load Capacity (kg)	700
Bearing Type	Ball
Fixing Option	Plate
Castor Type	Swivel
To Suit Fixing Bolt (mm)	10
Swivel Radius (mm)	165
Height (mm)	245
Plate Size (mm)	135 x 110
Hole Centres (mm)	140 X 105
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Polyurethane on Aluminium Rim / 75 Shore A
Tread (mm)	50
Top Plate Thickness (mm)	6
Temperature Resistance	-20 °C TO +70 °C
Fork Thickness (mm)	5

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

