
T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Softer Ergonomic Polyurethane Plate Swivel Castor 125mm 350kg Load



Product code: BZMJ125RSPABJ

Fabricated white zinc ROHS plated swivel castor with a top plate fixing fitted with a round ergonomic polyurethane tyred on aluminium centred wheel with ball bearings. Wheel diameter 125mm, tread width 41mm, overall height 165mm, top plate 138mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 350kg at 4kph

Diameter (mm)	125
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	165
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A
Temperature Resistance	-20 ?C TO +70 ?C
Top Plate Thickness (mm)	7
Fork Thickness (mm)	6
Swivel Radius (mm)	101
Load Capacity (kg)	350
Tread (mm)	41
Castor Material	Zinc plated