

Softer Ergonomic Polyurethane Plate Swivel Castor Brake 150mm 500kg Load

Product code: BZSAB150RSPABJSWB



Fabricated zinc plated swivel castor with plate fixing fitted with a blue 75 shore A polyurethane tyre aluminium centred wheel centred wheel with ball bearings and total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 250mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg ** FOR INTERNAL AND EXTERNAL TOWING USE**

| | |
|--------------------------|---|
| Diameter (mm) | 150 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Bearing Type | Ball |
| Height (mm) | 200 |
| Plate Size (mm) | 138 x 110 |
| Hole Centres (mm) | 105 x 80 |
| To Suit Fixing Bolt (mm) | 10 |
| Wheel Material | Polyurethane on Aluminium |
| Colour / Shore Hardness | Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Top Plate Thickness (mm) | 8 |
| Fork Thickness (mm) | 6 |
| Swivel Radius (mm) | 145 |
| Load Capacity (kg) | 500 |
| Tread (mm) | 50 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

