

## Softer Ergonomic Polyurethane Plate Swivel Castor Brake 200mm 600kg Load

**Product code: BZMJ200RSPABJSWB**

Fabricated steel swivel castor with a top plate fixing fitted with a blue 75 shore A ergonomic polyurethane tyred on aluminium centred wheel with a ball bearing with a total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 241mm, plate size 138mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 600kg at 4kph, 320kg at 10kph, 280kg at 16kph  
**\*\* FOR INTERNAL TOWING USE ONLY \*\***



Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	241
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A
Temperature Resistance	-20 °C TO +70 °C
Top Plate Thickness (mm)	7
Fork Thickness (mm)	6
Swivel Radius (mm)	156
Load Capacity (kg)	600
Tread (mm)	50