

Vulkollan Polyurethane Cast Iron Plate Fixed Castor 200mm 1400kg Load

Product code: BZQFX200VPTBJ

POA Fabricated fixed castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyre cast iron centred wheel with ball bearings. Wheel diameter 200mm, tread width 80mm, overall height 264mm, top plate 200mm x 160mm, hole centres 160mm x 120mm. Load capacity 1400kg at 6kph.



| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Fixed |
| Bearing Type | Ball |
| Height (mm) | 264 |
| Plate Size (mm) | 200 X 160 |
| Hole Centres (mm) | 160 X 120 |
| To Suit Fixing Bolt (mm) | 16 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Vulkollan Polyurethane on Cast Iron / 92 Shore A |
| Temperature Resistance | -30 °C TO +80 °C |
| Top Plate Thickness (mm) | 16 |
| Fork Thickness (mm) | 10 |
| Load Capacity (kg) | 1400 |
| Tread (mm) | 80 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

