

## Vulkollan Polyurethane Cast Iron Plate Fixed Castor 250mm 1700kg Load

**Product code: BZQF250VPTBJ**

**POA** Fabricated fixed castor with a flat plate fixing fitted with a High grade Vulkollan polyurethane tyre on cast iron centred wheel with a ball bearing. Wheel diameter 250mm, tread width 80mm, overall height 314mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 2130kg static, 1700kg at 6kph.. **\*\*MANUFACTURED TO ORDER\*\***



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Height (mm)	314
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Load Capacity (kg)	1700
Tread (mm)	80

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

