

## Vulkollan Polyurethane Cast Iron Plate Swivel Castor 200mm 1400kg Load

**Product code: BZQ200VPTBJ**



**POA** Fabricated swivel castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyre cast iron centred wheel with ball bearings. Wheel diameter 200mm, tread width 80mm, overall height 264mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1730kg static, 1400kg at 6kph. **\*\*MANUFACTURED TO ORDER\*\***

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	264
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	167
Load Capacity (kg)	1400
Tread (mm)	80

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

