

Vulkollan Polyurethane Cast Iron Plate Swivel Castor 250mm 1350kg Load

Product code: BZQ250VPTBJ/50/M



Fabricated swivel castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyred cast iron centred wheel with ball bearings. Wheel diameter 250mm, tread width 50mm, overall height 314mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1,350kg

Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	314
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	210
Load Capacity (kg)	1350
Tread (mm)	50

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

