

Vulkollan Polyurethane Cast Iron Plate Swivel Castor 250mm 1700kg Load

Product code: BZQX250VPTBJ

POA Fabricated swivel castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyre cast iron centred wheel with ball bearings. Wheel diameter 250mm, tread width 80mm, overall height 314mm, top plate 200mm x 160mm, hole centres 160mm x 120mm. Load capacity 1700kg at 6kph.



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	314
Plate Size (mm)	175 X 140
Hole Centres (mm)	160 X 120
To Suit Fixing Bolt (mm)	16
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	16
Fork Thickness (mm)	10
Swivel Radius (mm)	203
Load Capacity (kg)	1700
Tread (mm)	80

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

