

## Vulkollan Polyurethane Driven Wheel 150mm 670Kg Load

**Product code: VULW150-50-55-KM40**

Vulkollan polyurethane tyre on a colturiet painted cast iron centred wheel with a keyway. Diameter 150mm, Tread Width 50mm, Hub Width 55mm, Hub Diameter 70mm, Keyway Bore 40mm, Load Capacity 670kg. PLEASE NOTE Keyway Bore SIZE TOLERANCES ARE BASED ON H7 ( 0 +0.025 )  
DIN6885 ISO 286-2 STANDARD



|                         |                                                  |
|-------------------------|--------------------------------------------------|
| Wheel Material          | Polyurethane on Cast Iron                        |
| Diameter (mm)           | 150                                              |
| Hub Width (mm)          | 55                                               |
| Bore Size (mm)          | 40                                               |
| Tread (mm)              | 50                                               |
| Colour / Shore Hardness | Vulkollan Polyurethane on Cast Iron / 90 Shore A |
| Temperature Resistance  | -20 °C TO +80 °C                                 |
| Bearing Type            | Keywayed                                         |
| Hub Diameter (mm)       | 70                                               |
| Load Capacity (kg)      | 670                                              |

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

