

## Vulkollan Polyurethane Driven Wheel 300mm 1870Kg Load

**Product code: VULW300-75-80-KM60**



Vulkollan polyurethane tyre on a colturiet painted cast iron centred wheel with a keyway. Diameter 300mm, Tread Width 75mm, Hub Width 80mm, Hub Diameter 96mm, Keyway Bore 60mm, Load Capacity 1870kg. PLEASE NOTE Keyway Bore SIZE TOLERANCES ARE BASED ON H7 ( 0 +0.030 ) DIN6885 ISO 286-2 STANDARD

|                         |  |
|-------------------------|--|
| Wheel Material          | Polyurethane on Cast Iron                        |
| Diameter (mm)           | 300  |
| Hub Width (mm)          | 80   |
| Bore Size (mm)          | 60   |
| Tread (mm)              | 75   |
| Colour / Shore Hardness | Vulkollan Polyurethane on Cast Iron / 90 Shore A |
| Temperature Resistance  | -20 °C TO +80 °C                                 |
| Bearing Type            | Keywayed   |
| Hub Diameter (mm)       | 96   |
| Load Capacity (kg)      | 1870   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

