

## DRAWING DISCLAIMER

COPYRIGHT OF THIS DRAWING IS RESERVED BY BIL GROUP LTD. IT IS ISSUED ON CONDITION THAT IT IS NOT REPRODUCED, COPIED, OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF BIL GROUP LTD.









SSRAF50VGRBJBH10

Grade 304 Pressed stainless steel fixed castor with a 10mm bolt hole fitted with a grey thermoplastic rubber tyre on polypropylene centred wheel with ball bearings. Wheel diameter 50mm, tread width 24mm, overall height 74mm. Load capacity 50kg







	NAME	DATE
DRAWN	Matt	09/10/17
APPROVED BY	Kevin	09/10/17
SCALE	2:3	09/10/17
WEIGHT	0.149ka	09/10/17

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETRES

Unspecified Tolerances Machining ± 0.25mm Fabrication ± 1mm



BIL Group Ltd, Porte Marsh Road, Calne Wiltshire, SN11 9BW, United Kingdom Tel +44 (0)1249 822 222 Fax: +44 (0)1249 822 300 www.bilgroup.co.uk

REV

TITLE

SSRAF50VGRBJBH10

SIZE DWG NO.

BILCW03SSRAF50VGRBJBH10\_\_01

FILE NAME BILCW03SSRAF50VGRBJBH10\_01.PDF SHEET 1 OF 1